


# Coray CXR



- Lighting technology LED
  - Tool-less ceiling mounting
  - Ceiling cut-out Ø75 mm
  - Floor and wall mounting not permitted
  - Turning and tilting (355°/35°)
  - With integral reflector SSP, SP or MFL
  - Supply unit included
  - Connection to power supply by Wieland plug GST18i3; wire length l = 0.5 m
  - Version with DALI or Casambi on request (Casambi not compatible with metal ceilings)
- Colours: white, anthracite, silver on request



- 100% recyclable
- Designed in accordance with the Ecodesign Directive (2019/2020/EU)
- Long LED life due to efficient thermal management






## Photometric data

CRI Colour quality	Power level	
	9 W	
	Luminous flux luminaire [lm]	System efficiency [lm/W]
830	600	67
840	600	67
927	500	56
930	500	56

Maximum possible, optionally available connected load: 9 W.

According to IEC 62722-1 the given rated values of the total luminous flux and of the electric power must not deviate by more than 10%. The photometric values are

standard values and refer to the entire luminaire. Other light qualities on request to [info@ansorg.com](mailto:info@ansorg.com). This product contains two light sources of energy efficiency class D (830/840) or E (927/930).



## Technical data

Information	Values
Connection data	48 V/DC, 9 W
Weight	approx. 0.2 kg
Colour tolerance	3SDCM (MacAdam)
Lumen maintenance	L80/B10 ≥ 50,000h, Ta 25 °C
	L90/B50 ≥ 50,000h, Ta 25 °C
Failure rate	C0/B10 ≥ 50,000h, Ta 25 °C
Photobiological safety	RG2
Number per circuit breaker B 16A	25
Protection class	1
Type of protection	IP20

## Optional accessories

Product	Option
Lentille convergente interchangeable	SSP, SP, MFL