


Iqona ILM



- Lighting technology LED
 - Tool-less mounting with track adapter for three-circuit track
 - Floor and wall mounting not permitted
 - Turning and tilting (360°/110°)
 - With integral reflector SSP, SP, MFL, FL or WFL
 - Supply unit included
 - Version with DALI or Casambi on request
- Colours: white, anthracite, silver on request



- 100% recyclable
- Designed in accordance with the Ecodesign Directive (2019/2020/EU)
- Long LED life due to efficient thermal management








Photometric data

CRI Colour quality	Power level					
	30 W		34 W		40 W	
	Luminous flux luminaire [lm]	System efficiency [lm/W]	Luminous flux luminaire [lm]	System efficiency [lm/W]	Luminous flux luminaire [lm]	System efficiency [lm/W]
830	3989	133	4417	129	5029	125
840	4200	140	4651	136	5295	132
927	3250	108	3599	105	4097	102
930	3433	114	3802	111	4328	108
940	3599	120	3985	117	4536	113
Brilliant (930 = Best color/ Best White)	3251	108	3586	105	4052	101
N27	2388	79	2633	77	2976	74
Meat	1922	64	-	-	2374	59
NMeat	1529	51	-	-	1904	47

Maximum possible, optionally available connected load: 48 W.
According to IEC 62722-1 the given rated values of the total luminous flux and of the electric power must not deviate by more than 10%. The values apply to the luminaire with MFL reflector, in the case of the SSP/SP/FL/WFL reflectors the

values can deviate +/- 5%. The photometric values are standard values and refer to the entire luminaire. Other light qualities on request to info@ansorg.com. This product contains two light sources of energy efficiency class D (830/840), E (927/930/940), F (N27) or G (NMeat).



Technical data

Information	Values
Connection data	220-240 V, 50/60 Hz (110-277 V on request)
Weight	approx. 1.1 kg
Colour tolerance	3SDCM (MacAdam)
Lumen maintenance	L80/B10 ≥ 50,000h, Ta 25 °C L90/B50 ≥ 50,000h, Ta 25 °C
Failure rate	C0/B10 ≥ 50,000h, Ta 25 °C
Photobiological safety	RG1
Number per circuit breaker B 16A	25
Protection class	1
Type of protection	IP20
Certification mark	ENEC / CB